



Link

Wall Light


1


255x75
(220x55)
Open Face | Luminaire


255x75
(220x55)
Wallbox


2


255x75
(220x55)
Grill Face | Luminaire


255x75
(220x55)
Wallbox

		LED Power	Lumens (at 3000K)	Beam	Weight	IK Rating	Driver Options
1	Open Face	10W (24V DC)	326lm	105°	742g	IK08	Phase Cut, DALI, Bluetooth
2	Grill Face	10W (24V DC)	112lm	105°	784g	IK10	Phase Cut, DALI, Bluetooth

Key Information		Design		Performance		Driver	
Mounting	Wall Recessed	Material	Powder Coated Aluminium, PVC Wall Box	Lumen efficacy	Up to 32lm/W	Non-Dim	Remote, wired in parallel
Finish	<div><div></div> Textured Black</div> <div><div></div> Textured White</div> <div><div></div> Textured Grey</div>	IP Rating	IP65	CRI (Ra/R9)	80+ (R9:>0)	Phase Cut	Remote, wired in parallel
LED CCT	<div><div></div> 3000K</div> <div><div></div> 4000K</div>	Class Rating	Class III	Lifetime (Ta 25°C)	>54,000h L70B10	DALI	Remote, wired in parallel
Warranty	3 Years			Ambient Temperature Range	10°- 30°C	Bluetooth	Remote, wired in parallel
				SDCM	≤3		

