


		LED Power	Lumens (at 3000K)	Beam	Beam (Elliptical)	Weight	Lumen Efficacy
1	Mini	3W (1000mA)	206lm	6° 15° 40°	10x60° 15x60° 35x60°	230g	Up to 41lm/W
2	Small	8W (200mA)	607lm	11° 21° 45°	12x55° 20x60° 40x60°	450g	Up to 70lm/W
	Small Wallwasher	8W (200mA)	508lm	45° Asymmetrical	-	450g	Up to 58lm/W
3	Medium	15W (400mA)	1398lm	22° 40° 60°	22x60° 40x70° 50x70°	680g	Up to 91lm/W
	Medium Wallwasher	15W (400mA)	1195lm	60° Asymmetrical	-	680g	Up to 77lm/W

Key Information		Design		Performance		Driver	
Mounting	Ceiling Recessed	Product Family	ION	CRI (Ra/R9)	92+ (R9: >50)	Phase Cut	Remote
Body Finish	☒ Textured Black ☐ Textured White	Adjustability	80° Tilt (Fully retracted), 355° Rotation	UGR (70/50/20)	<13, Mini: <10	DALI	Remote
Baffle Finish	☒ Matt Black ☐ Matt White ☒ Stealth Metallic ☐ Matt Gold	Material	Powder Coated Aluminium	Lifetime (Ta 25°C)	>72,000h L90B10, Mini: >31,000h L90B10	Bluetooth	Remote
Baffle finish not applicable for wallwashers.		IP Rating	IP20	Operating Ambient Temperature	-10°- 35°C	Driver Notes <i>Bluetooth is not compatible with the Mini model.</i>	
LED CCT	☒ 2700K ☐ 3000K ☐ 4000K ☒ 2700K-6500K (Tunable White)	Class Rating	Class II	SDCM	≤2, Mini: ≤3		
Warranty	5 Years	Insulation Rating	CA90	COI Compliance Model Requirements	4000K		



Available Accessories
Linear Lens (for elliptical beams)
Honeycomb Lens (for reduced glare)
Softening Lens (for softening beam edges)

