



		LED Power	Lumens (at 3000K)	Beam	Weight	DALI Addresses
1 4	Small Direct	22W	1,960lm	90°	3.2kg	1
	Small Direct/Indirect	22W ↓   11W ↑	3,093lm (1,960lm ↓   1,133lm ↑)	90° ↓   120° ↑	4kg	2
2 5	Medium Direct	48W	4,721lm	90°	8.1kg	2
	Medium Direct/Indirect	48W ↓   22W ↑	7,001lm (4,721lm ↓   2,280lm ↑)	90° ↓   120° ↑	9.1kg	2
3 6	Large Direct	96W	9,606lm	90°	16.7kg	2
	Large Direct/Indirect	96W ↓   48W ↑	14,432lm (9,606lm ↓   4,826lm ↑)	90° ↓   110° ↑	17.8kg	3

Key Information		Design		Performance		Control	
Mounting	Ceiling Suspended	Product Family	Akira G2	Lumen Efficacy	Up to 102lm/W	Phase Cut	Built-in
Finish	<div><div></div> Textured Black</div> <div><div></div> Textured White</div>	Material	Powder Coated Aluminium	CRI (Ra/R9)	90+ (R9: >50)	DALI	Built-in
LED CCT	<div><div></div> 3000K</div> <div><div></div> 4000K</div>	Direct Optics	Micro Prismatic Lens	UGR	<19	Bluetooth	Built-in
Warranty	5 Years	Indirect Optics	Elliptical Spread Lens	Luminance(L65)	≤2000cd/m²		
		IP Rating	IP40	Lifetime (Ta 25°C)	>53,000h L90B10		
		Class Rating	Class I	Power Factor	≥0.9		
				Operating Ambient Temperature	-10°- 35°C		
				SDCM	≤3		

