



Left: Residential wall application
Top & Above: 350° of adjustability


Helix

WALL LIGHT

The simple wall light has been revitalised with a deceptively minimal single and double adjustable arm design in the Helix Wall Light. The design maximises adjustability whilst maintaining a slim profile to gel with all bathroom design schemes. Each arm can rotated independently up to 350° for precise illumination in all desired directions.

- Ideal for vanity applications and feature corridor lighting with a CRI rating of 90+
- Rotates facing outwards for excellent task lighting, whilst face inwards for soft indirect lighting
- Suitable for horizontal and vertical applications
- Available in single or double arm configurations

Single
Measurements (mm)




Absolute Luminous Flux
5W (400mA) 405lm (at 3000K) 410lm (at 4000K)
Beam
90° (F)

Finishes
UV Textured Black
UV Textured White

General Specifications
Material Powder Coated Aluminium, Frosted Acrylic Diffuser
IP 44
Warranty 3 Years

LED
Colour Temp 3000K, 4000K
CRI 90+
Efficacy Up to 69lm/w
Colour Deviation SDCM≤3
Lifetime 59,000h L70

Twin
Measurements (mm)




Absolute Luminous Flux
10W (400mA) 745lm (at 3000K) 825lm (at 4000K)
Beam
90° (F)

Driver
Power Factor >0.90
240V Built-in Non-Dimmable Driver
Dimming DALI Dim Optional (DALI driver must be remote)

Notes
Installation requires 30mm space above and below luminaire.

Photometrics



α = 90°



A	B	C	D	E	F	A	Product Family	B	Power	C	Finish	D	CCT	E	Beam	F	Driver (DALI drivers can be configured via Product Toolbox)
HELX	0005	TB	30	F	-	HELX	Helix Single Vanity Light	0005	5W	TB	Textured Black	30	3000K		Flood	-	Standard Non-Dimmable Driver included
HELT						HELT	Helix Twin Vanity Light	0010	10W	TW	Textured White	40	4000K				

Example: **HELX0005.TB30.F**
Refer to data sheet for available configurations.
Visit Product Toolbox at unios.com/helix to configure compatible Osram/Tridonic DALI drivers.