




ION R

Downlight



	LED Power	Lumens (at 3000K)	Beam	Beam (Elliptical)	Weight	Driver Options	Lumen Efficacy
1 Small	9W (250mA)	963lm	22° 40° 60°	20x60° 30x70° 50x80°	310g	Phase Cut, DALI, Bluetooth	Up to 93lm/W
	11W (300mA)	1155lm					
	15W (400mA)	1548lm					
2 Medium	13W (350mA)	1355lm	22° 40° 60°	20x60° 30x70° 50x80°	456g	Phase Cut, DALI, Bluetooth	Up to 100lm/W
	15W (400mA)	1548lm					
	22W (600mA)	2392lm					
3 Large	27W (750mA)	2990lm	30° 50° 70°	30x70° 50x80° 60x90°	1108g	Phase Cut, DALI, Bluetooth	Up to 98lm/W
	32W (900mA)	3587lm					
	36W (1000mA)	3973lm					
4 XL	43W (1200mA)	4767lm	30° 50° 70°	30x70° 50x80° 60x90°	1822g	Non-Dim, DALI, Bluetooth	Up to 105lm/W
	43W (1200mA)	4767lm					
	43W (1200mA)	4767lm					
5 Medium Wallwasher	13W (350mA)	760lm	50° Asymmetrical	-	456g	Phase Cut, DALI, Bluetooth	Up to 56lm/W
	15W (400mA)	868lm					
	22W (600mA)	1194lm					
6 Large Wallwasher	27W (750mA)	1493lm	50° Asymmetrical	-	1108g	Phase Cut, DALI, Bluetooth	Up to 49lm/W
	27W (750mA)	1493lm					
	32W (900mA)	1792lm					

Key Information		Design		Performance		Driver	
Mounting	Ceiling Recessed	Product Family	ION	CRI (Ra/R9)	92+ (R9: >50)	Non-Dim	Remote
Trim Finish	<input type="checkbox"/> Textured Black <input type="checkbox"/> Textured White	Material	Powder Coated Aluminium	UGR	<13	Phase Cut	Remote
Baffle Finish	<input type="checkbox"/> Matt Black <input type="checkbox"/> Matt White <input type="checkbox"/> Stealth Metallic <input type="checkbox"/> Matt Gold*	IP Rating	IP54 (Room Side)	Lifetime (Ta 25°C)	>55,000h L90B10	DALI	Remote
	*Available in small and medium model	Class Rating	Class II	Ambient Temperature Range	-10°- 30°C	Bluetooth	Remote
Wallwasher Baffle Finish	<input checked="" type="checkbox"/> Stealth Metallic	Insulation Rating	Small, Medium: IC-4 Large, XL: CA90	SDCM	≤2		
LED CCT	<input type="checkbox"/> 2700K <input type="checkbox"/> 3000K <input type="checkbox"/> 4000K <input type="checkbox"/> 2700K-6500K (Tunable White)			COI Compliance model requirements	4000K		
Warranty	5 Year						



Available Accessories

- Tension clips (for concrete applications, Medium size only)
- Linear Lens (for elliptical beams)
- Honeycomb Lens (for reduced glare)
- Softening Lens (for softening beam edges)
- Seismic Lanyard


Notes

For 22° beam options, an anti-glare louvre is included to aid in beam control and glare (for small and medium only)




ION R

Surface Mounted Downlight



	LED Power	Lumens (at 3000K)	Beam	Beam (Elliptical)	Weight	Driver Options	Lumen Efficacy
1 Small	11W (300mA)	1155lm	22° 40° 60°	20x60° 30x70° 50x80°	714g	Phase Cut, DALI, Bluetooth	Up to 93lm/W
2 Medium	15W (400mA)	1548lm	22° 40° 60°	20x60° 30x70° 50x80°	955g	Phase Cut, DALI, Bluetooth	Up to 100lm/W
3 Large	32W (900mA)	3587lm	30° 50° 70°	30x70° 50x80° 60x90°	2278g	Phase Cut, DALI, Bluetooth	Up to 98lm/W
4 XL	43W (1200mA)	4767lm	30° 50° 70°	30x70° 50x80° 60x90°	3550g	Non-Dim, DALI, Bluetooth	Up to 105lm/W
5 Medium Wallwasher	15W (400mA)	868lm	50° Asymmetrical	-	955g	Phase Cut, DALI, Bluetooth	Up to 56lm/W
6 Large Wallwasher	32W (900mA)	1792lm	50° Asymmetrical	-	2278g	Phase Cut, DALI, Bluetooth	Up to 49lm/W

Key Information		Design		Performance		Driver	
Mounting	Ceiling Surface	Product Family	ION	CRI (Ra/R9)	92+ (R9: >50)	Non-Dim	Built-in
Canister Finish	<input checked="" type="checkbox"/> Textured Black <input type="checkbox"/> Textured White	Material	Powder Coated Aluminium	UGR	<13	Phase Cut	Built-in
Baffle Finish	<input checked="" type="checkbox"/> Matt Black <input type="checkbox"/> Matt White <input checked="" type="checkbox"/> Stealth Metallic <input type="checkbox"/> Matt Gold*	IP Rating	IP44	Lifetime (Ta 25°C)	>55,000h L90B10	DALI	Built-in
		Class Rating	Class I	Ambient Temperature Range	-10°- 30°C	Bluetooth	Remote
		SDCM	≤2	COI Compliance model requirements	4000K		
*Available in small and medium model							
Wallwasher Baffle Finish	<input checked="" type="checkbox"/> Stealth Metallic						
LED CCT	<input checked="" type="checkbox"/> 2700K <input type="checkbox"/> 3000K <input type="checkbox"/> 4000K <input checked="" type="checkbox"/> 2700K-6500K (Tunable White)						
Warranty	5 Year						




Available Accessories
 Linear Lens (for elliptical beams)
 Honeycomb Lens (for reduced glare)
 Softening Lens (for softening beam edges)

Notes
 For 22° beam options, an anti-glare louvre is included to aid in beam control and glare (for small and medium only)




ION R

Suspended Downlight



	LED Power	Lumens (at 3000K)	Beam	Beam (Elliptical)	Weight	Driver Options	Lumen Efficacy
1 Small	11W (300mA)	1155lm	22° 40° 60°	20x60° 30x70° 50x80°	1214g	Phase Cut, DALI, Bluetooth	Up to 93lm/W
2 Medium	15W (400mA)	1548lm	22° 40° 60°	20x60° 30x70° 50x80°	1455g	Phase Cut, DALI, Bluetooth	Up to 100lm/W
3 Large	32W (900mA)	3587lm	30° 50° 70°	30x70° 50x80° 60x90°	2778g	Phase Cut, DALI, Bluetooth	Up to 98lm/W
4 XL	43W (1200mA)	4767lm	30° 50° 70°	30x70° 50x80° 60x90°	4050g	Non-Dim, DALI, Bluetooth	Up to 105lm/W
5 Medium Wallwasher	15W (400mA)	868lm	50° Asymmetrical	-	1455g	Phase Cut, DALI, Bluetooth	Up to 56lm/W
6 Large Wallwasher	32W (900mA)	1792lm	50° Asymmetrical	-	2778g	Phase Cut, DALI, Bluetooth	Up to 49lm/W

Key Information		Design		Performance		Driver	
Mounting	Ceiling Suspended	Product Family	ION	CRI (Ra/R9)	92+ (R9: >50)	Non-Dim	Built-in
Canister Finish	<input checked="" type="checkbox"/> Textured Black <input type="checkbox"/> Textured White	Material	Powder Coated Aluminium	UGR	<13	Phase Cut	Built-in
Baffle Finish	<input checked="" type="checkbox"/> Matt Black <input type="checkbox"/> Matt White <input checked="" type="checkbox"/> Stealth Metallic <input type="checkbox"/> Matt Gold*	IP Rating	IP20	Lifetime (Ta 25°C)	>55,000h L90B10	DALI	Built-in
		Class Rating	Class I	Ambient Temperature Range	-10°- 30°C	Bluetooth	Remote
		SDCM	≤2	COI Compliance model requirements	4000K		
*Available in small and medium model							
Wallwasher Baffle Finish	<input checked="" type="checkbox"/> Stealth Metallic						
LED CCT	<input checked="" type="checkbox"/> 2700K <input type="checkbox"/> 3000K <input type="checkbox"/> 4000K <input checked="" type="checkbox"/> 2700K-6500K (Tunable White)						
Warranty	5 Year						



Available Accessories
 Linear Lens (for elliptical beams)
 Honeycomb Lens (for reduced glare)
 Softening Lens (for softening beam edges)

Notes
 For 22° beam options, an anti-glare louvre is included to aid in beam control and glare




ION R

Vandal-proof Downlight



	LED Power	Lumens (at 3000K)	Beam	Weight
1 Vandal-proof	22W (600mA)	2391lm	30° 50° 70°	1356g
	27W (750mA)	2989lm		
	32W (900mA)	3587lm		

Key Information		Design		Performance		Driver	
Mounting	Ceiling Recessed	Product Family	ION	Lumen efficacy	Up to 100lm/W	Phase Cut	Remote
Trim Finish	<input type="checkbox"/> Textured Black <input type="checkbox"/> Textured White	Material	Powder Coated Aluminium	CRI (Ra/R9)	92+ (R9: >50)	DALI	Remote
Baffle Finish	<input type="checkbox"/> Matt Black <input type="checkbox"/> Matt White <input type="checkbox"/> Stealth Metallic	IP Rating	IP65	UGR	<13	Bluetooth	Remote
LED CCT	<input type="checkbox"/> 2700K <input type="checkbox"/> 3000K <input type="checkbox"/> 4000K <input type="checkbox"/> 2700K-6500K (Tunable White)	IK Rating	IK10	Lifetime (Ta 25°C)	>55,000h L90B10		
Warranty	5 Year	Class Rating	Class II	Ambient Temperature Range	-10°- 30°C		
		Insulation Rating	CA90	SDCM	≤2		
				COI Compliance model requirements	4000K		



Available Accessories
Seismic Lanyard




ION R

Adjustable Downlight



	LED Power	Lumens (at 3000K)	Beam	Beam (Elliptical)	Weight	Lumen Efficacy
1 Small	7W (200mA)	659lm	12° 30° 50°	12x60° 30x60° 40x70°	355g	Up to 72lm/W
2 Medium	9W (250mA)	899lm	22° 40° 60°	20x60° 35x70° 50x70°	600g	Up to 90lm/W
	13W (350mA)	1258lm				
3 Large	22W (600mA)	2237lm	30° 45° 60°	30x70° 45x60° 60x80°	1310g	Up to 95lm/W
	29W (800mA)	2982lm				

Key Information		Design		Performance		Driver	
Mounting	Ceiling Recessed	Product Family	ION	CRI (Ra/R9)	92+ (R9: >50)	Non-Dim	Remote
Trim Finish	<input type="checkbox"/> Textured Black <input type="checkbox"/> Textured White	Adjustability	355° Rotation 25° Tilt	UGR	<13	Phase Cut	Remote
Baffle Finish	<input type="checkbox"/> Matt Black <input type="checkbox"/> Matt White <input type="checkbox"/> Stealth Metallic <input type="checkbox"/> Matt Gold*	Material	Powder Coated Aluminium	Lifetime (Ta 25°C)	>55,000h L90B10	DALI	Remote
	<i>*Available in small and medium model</i>	IP Rating	IP54 (Room Side)	Ambient Temperature Range	-10°- 30°C	Bluetooth	Remote
LED CCT	<input type="checkbox"/> 2700K <input type="checkbox"/> 3000K <input type="checkbox"/> 4000K <input type="checkbox"/> 2700K-6500K (Tunable White)	Class Rating	Class II	SDCM	≤2		
Warranty	5 Year	Insulation Rating	Small, Medium: IC-4 Large: CA90	COI Compliance model requirements	4000K		



Available Accessories
Linear Lens (for elliptical beams)
Honeycomb Lens (for reduced glare)
Softening Lens (for softening beam edges)
Seismic Lanyard

Notes
For 12° and 22° beam options, an anti-glare louvre is included to aid in beam control and glare (for small and medium only)




ION R Focus

Downlight



	LED Power	Lumens (at 3000K)	Beam	Beam (Elliptical)	Weight
1 Focus	7W (200mA)	593lm	12° 30° 50°	12x30° 30x60° 50x70°	355g

Key Information		Design		Performance		Driver	
Mounting	Ceiling Recessed	Product Family	ION	Lumen efficacy	Up to 67lm/W	Non-Dim	Remote
Trim Finish	<input type="checkbox"/> Textured Black <input type="checkbox"/> Textured White	Material	Powder Coated Aluminium	CRI (Ra/R9)	92+ (R9: >50)	Phase Cut	Remote
LED CCT	<input type="checkbox"/> 2700K <input type="checkbox"/> 3000K <input type="checkbox"/> 4000K <input type="checkbox"/> 2700K-6500K (Tunable White)	IP Rating	IP54 (Room Side)	UGR	<10	DALI	Remote
Warranty	5 Year	Class Rating	Class II	Lifetime (Ta 25°C)	>55,000h L90B10	Bluetooth	Remote
		Insulation Rating	IC-4	Ambient Temperature Range	-10°- 30°C		
				SDCM	≤2		
				COI Compliance model requirements	4000K		



ION R Accent

Downlight



	LED Power	Lumens (at 3000K)	Beam	Beam (Elliptical)	Weight
1 Accent	7W (200mA)	593lm	12° 30° 50°	12x30° 30x60° 50x70°	355g

Key Information		Design		Performance		Driver	
Mounting	Ceiling Recessed	Product Family	ION	Lumen efficacy	Up to 67lm/W	Non-Dim	Remote
Trim Finish	<input type="checkbox"/> Textured Black <input type="checkbox"/> Textured White	Adjustability	355° Rotation 25° Tilt	CRI (Ra/R9)	92+ (R9: >50)	Phase Cut	Remote
LED CCT	<input type="checkbox"/> 2700K <input type="checkbox"/> 3000K <input type="checkbox"/> 4000K <input type="checkbox"/> 2700K-6500K (Tunable White)	Material	Powder Coated Aluminium	UGR	<10	DALI	Remote
Warranty	5 Year	IP Rating	IP54 (Room Side)	Lifetime (Ta 25°C)	>55,000h L90B10	Bluetooth	Remote
		Class Rating	Class II	Ambient Temperature Range	-10°- 30°C		
		Insulation Rating	IC-4	SDCM	≤2		
				COI Compliance model requirements	4000K		

