

unios®



PRODUCT GUIDE

Inter Linear
Collection





Our latest take on linear

With refined profiles, lasting performance,
and leading colour consistency, the Inter Linear
Collection is built for spaces that demand
precision from day one, and for years to come.



A new era

Overview

Superior colour consistency.

≤ 1 SDCM

An expansive array of application possibilities.



12 Profiles

Cut-to-length, with a reduced lead time.

5 days

Innovation without inflation

30% more cost effective than previous linear

Discover

Product

Inter Strip →10

Inter Profiles →12


Product Summary →42

Tools

Applications →26

Wiring Guide →36

Selection Guide →40





Crafted in Australia

Architectural-grade linear lighting, supplied to custom lengths with fast local turnaround, engineered to minimise failure and latent damage.

Cut-to-Length

Exact project lengths are provided for further on-site customisation.

5 Days

Ready to dispatch in 5 days or less.

ESD-Protected

Fabricated in an ESD-free environment with on-site tools to prevent latent damage to the final product.




Inter Strip

The Inter Strip Light is the foundation of the collection, engineered for colour accuracy and a lifetime of performance.

Inter Strip IN10 pairs with 11 Inter profiles, simplifying selection and installation.


The Inter Strip IN5 fits perfectly into the ultra-mini Inter Pro PS10 profile, ideal for cabinetry and fine accents.

Single CCT




160 LEDs/m Pg. 54


Tunable White



240 LEDs/m Pg. 55




160 LEDs/m Pg. 54




180 LEDs/m Pg. 55

RGB




120 LEDs/m Pg. 56



120 LEDs/m Pg. 56

RGBW



240 LEDs/m Pg. 57

6.25mm of finer details.

The Single CCT Strips are customisable within 6.25mm increments, and RGB/RGBW strips within 50mm increments.

≤1 SDCM

SDCM≤1 on Single CCT and Tunable White Strips, and SDCM≤2 on RGBW Strips for superior colour consistency.

CRI95+ R9>90

TM30 Rf94 / Rg101

Colour accuracy across the spectrum, with truer reds than ever.

RGB
or RGBW

A pop of colour can do wonders in transforming a space and building atmosphere.

>50,000h
L90B10

Extended lifetime you can trust – install once, forget the rest.

2700K
– 6500K


Adaptable for comfort, mood, and circadian rhythm.

Simplified
Selections

Compatible with 11 Inter profiles, IN10 keeps your selections simple while covering a wide range of applications.

10

Profile Overview





Inter Pro

A true all-rounder, the Inter Pro provides dot-free illumination for a variety of applications.




The Inter PS10 is ultra-mini, ideal for installation in cabinetery and shelves.

The PS17 and PR22 are suitable for surface-mounted and recessed applications for cabinetery and island benches.

The Inter PS35 can be suspended atop work surfaces as a task light or surface-mounted along hallways.

For PS35 and PS50, use two IN10 strip lights at 15W/m to achieve 30W/m or 1494lm/m.


Inter Pro PS10



Surface Recessed

<547lm/m Pg. 42


Inter Pro PS17



Surface Recessed

<1307lm/m Pg. 43


Inter Pro PR22



Recessed

<1307lm/m Pg. 44



Inter Pro PS35



Surface Suspended

<1494lm/m Pg. 45

Inter Pro PR50



Recessed

<1494lm/m Pg. 46


Inter Flat

With exceptional output, the Inter Flat is ideal when used as an indirect light source.

Offers a high lumen output of up to 1694lm/m, ideal as an indirect light source that provides surface illumination, filling the space with reflected light.

Suitable for uplighting applications, such as on ceilings or behind-bedhead accents.


Inter Flat **FS17**



Surface <1694lm/m


Pg. 47

Inter Flat **FR25**



Recessed <1694lm/m

Pg. 48





Inter Angled


An angled profile set at 45°, designed for smooth directional or indirect illumination.

Ideal for wardrobes, joinery, or shelving to highlight clothing or objects without casting shadows or glare.

Perfect for uplighting, where you want to bring a soft gradient of light into the space.

Nestles discreetly into corners for a clean, integrated finish.

Inter Angled AS16



Surface <1783lm/m

Pg. 49




Inter Cove

Achieve a seamless, consistent finish with less time and lower costs than traditional hand-built methods.

Ensures optimal light distribution with no light waste, creating that gentle curtain of light along the wall.

Inter Cove CR100



Recessed <507lm/m

Pg. 50






Inter Round

The Round profile can be surface-mounted along walls, suspended above kitchen islands or bar tables for task lighting.


Create a subtle nod to the neon tube aesthetics when paired with IN10 RGB or RGBW Strips.

Inter Round RP30



Surface Suspended

<2078lm/m Pg. 51




Inter Dome

The Dome achieves forward and side illumination, thus lighting the verticals and surrounding surfaces.


By casting light across adjacent surfaces, the Dome reduces contrast and improves the perception of brightness and openness in the room.

Inter Dome DRS20 Inter Dome DSS20



Surface <1973lm/m

Pg. 52



Surface <1973lm/m

Pg. 53





In Application

Bar Setting

In this bar setting, the Inter layers indirect ambience, comfortable task light, and shelf and underbar accents for a welcoming space.

Inter Round RP30: In this bar setting, the Inter layers indirect ambience, comfortable task lighting, with shelf and underbar accents to create a welcoming space.

Inter Flat FS17: A high-output, low-profile linear concealed above the shelving for a gentle wash of indirect wall-and-ceiling ambient light.

Inter Pro PS10: Illuminates shelves and adds a soft under-bar glow, creating ambience and subtly guiding movements.

Inter Round RP30 Inter Flat FS17



Surface Suspended
<2078lm/m Pg. 51



Surface <1694lm/m
Pg. 47

Inter Pro PS10



Surface Recessed
<547lm/m Pg. 42

In Application

Hotel Room Setting

Within hotel rooms, Inter provides a welcoming ambience and subtle visual guidance, drawing attention to the essentials of a stay.

Inter Cove CR100: Casts gentle ambient light downwards and draws attention to the texture of surrounding finishes.

Inter Pro PS10: Discreet yet practical, the PS10 lights cabinetry and vanity areas, showcasing amenities and creating a warm and cosy feel.

Inter Cove CR100



Recessed <507lm/m

Pg. 50

Inter Pro PS10



Surface Recessed

<547lm/W Pg. 42





In Application

Retail Setting

In this retail space, a combination of Inter profiles is used to provide visibility, comfort and atmosphere.

Inter Dome DSS20: Surface-mounted to complement architectural lines while providing ambient light that sets a welcoming tone throughout the store.

Inter Pro PS17: Integrates into shelving to highlight merchandise with even illumination, while also accenting the counter's geometry and materials.

Inter Cove CR100: Recessed within the ceiling to deliver a gentle wash that softens contrasts and enriches the overall shopping atmosphere.

Inter Dome DSS20 Inter Pro PS17



Surface <1973lm/m

Pg. 53



Surface Recessed

<1307lm/m Pg. 43

Inter Cove CR100




Recessed <507lm/m

Pg. 50



Above – Ideal Profile: Inter Angled AS16 Linear Light

Left –Ideal Profile: Inter Round RP30 Linear Light



Above – Ideal Profile: Inter Cove CR100 Linear Light (Ceiling), Inter Pro PS10 Linear Light (Shelves)



Left – Ideal Profile: Inter Pro PR22
Linear Light (Ceiling), Inter Pro PS10
Linear Light (Shelves)



Right – Ideal Profile: Inter Pro PS35
Linear Light

Far Right – Ideal Profile: Inter Pro
PS35 Linear Light (Ceiling), Inter
Pro PS17 Linear Light (Column)



A wiring guide to the Inter Linear Light

To explain how you can approach different wiring methods with the Inter, we have created a few scenarios with varying project requirements and conditions.

For demonstrative purpose, we have used the IN10 Inter Strip Light at 10W/m as our example. However, the wiring processes and methods presented below apply to all Inter Strip models.

Before wiring an Inter product, there are two main pieces of information that you'd need to know:


The **Required Length**, which depends on your project's needs and requirements.

The **Maximum Single Length Run of your Inter Strip Light product** (refer to the table below).

Product	Wattage	Maximum Single Length Run
IN5 / IN10	5W/m	20m
IN5 / IN10	10W/m	10m
IN10	15W/m	6.5m
IN10	20W/m	5m
IN5 / IN10 (Tunable White/ RGB/RGBW)	N/A	5m

Example 1: When the Required Length does not exceed the Maximum Single Length Run.

The below illustration demonstrates a simple application of the Inter where Required Length does not exceed the Maximum Single Length Run.



Luminaire
Inter Strip Light IN10
Power: 10W/m

Requirements	
Total Required Length	10m
Maximum Single Length Run	10m
Maximum Manufactured Length	20m
Required Wattage	100W

Application (Below)	
Total Length	10m
Maximum Single Length Run	10m
Driver: 1 x 120W 24V DC Driver (Non-dim)	

Example 2: When the Required Length exceeds the Maximum Single Length Run.


Using a single driver

The below illustration demonstrates a scenario where the Required Length exceeds the Maximum Single Length Run, but does not exceed the driver capacity. It is suitable for when you can run extra cable to achieve the application.

Luminaire
Inter Strip Light IN10
Power: 10W/m

Requirements	
Total Required Length	20m
Maximum Single Length Run	10m
Maximum Manufactured Length	20m
Required Wattage	200W

Application (Below)	
Total Length	20m
Maximum Single Length Run	10m
Driver: 1 x 240W 24V DC Driver (Non-dim)	



Example 3: When the Required Length exceeds the driver capacity and the Maximum Single Length Run.


Using two drivers

The below illustration demonstrates a scenario where the Required Length exceeds the Maximum Single Length Run. It also exceeds the driver capacity, which require splitting the load into two drivers. Alternatively, the application is suitable for when you cannot run long cables between the driver and power entry.

Luminaire
Inter Strip Light IN10
Power: 10W/m


Requirements	
Total Required Length	30m
Maximum Single Length Run	10m
Maximum Manufactured Length	20m
Required Wattage	300W

Application (Below)	
Total Length	30m
Maximum Single Length Run	10m
Driver:	
1x 240W 24V DC Driver (Non-dim)	
1x 120W 24V DC Driver (Non-dim)	




On-Site Assembly

- 1 Specify your length for Unios to pre-cut LED strip in an ESD-free environment.



























- 2 Cut aluminium profile on-site for a perfect fit. Use roller tool to apply LED strip into profile.




Inter Linear Series

Selection Guide

The selection process for our large range of profiles can be quite daunting. With each profile made to cover different needs in different types of projects, we have created a selection matrix below to assist you in choosing a profile that will best suit your requirements.

	<div>PS10</div> Inter Pro	<div>PS17</div> Inter Pro	<div>PR22</div> Inter Pro	<div>PS35</div> Inter Pro	<div>PR50</div> Inter Pro	<div>FS17</div> Inter Flat	<div>FR25</div> Inter Flat	<div>AS16</div> Inter Angled	<div>CR100</div> Inter Cove	<div>RP30</div> Inter Round	<div>DR520</div> Inter Dome	<div>DSS20</div> Inter Dome	
													
													
Mounting	Surface Mounted, Recessed	Surface Mounted, Recessed	Recessed	Surface Mounted, Suspended	Recessed	Surface Mounted	Recessed	Surface Mounted	Recessed	Surface Mounted, Suspended	Surface Mounted	Surface Mounted	
Finish	<div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div></div>	<div><div></div></div>	<div><div></div><div></div></div>	<div><div></div><div></div></div>	<div><div></div></div>	<div><div></div></div>	<div><div></div></div>	<div><div></div></div>
Diffuser	Opal	Opal	Opal	Opal	Opal	Opal	Opal	Opal	Opal	Opal	Opal	Opal	
Strip Compatibility	IN5	IN10	IN10	IN10, 2X IN10 (at max 15W/m)	IN10, 2X IN10 (at max 15W/m)	IN10	IN10	IN10	IN10	IN10	IN10	IN10	
Power (per metre)	10W	5W-20W	5W-20W	5W-30W	5W-30W	5W-20W	5W-20W	5W-20W	5W-20W	5W-20W	5W-20W	5W-20W	
Absolute Luminous Flux (per metre at 3000K)	Up to 547lm/m	Up to 1307lm/m	Up to 1307lm/m	Up to 1494lm/m	Up to 1494lm/m	Up to 1694lm/m	Up to 1694lm/m	Up to 1783lm/m	Up to 507lm/m	2078lm/m	Up to 1973lm/m	Up to 1973lm/m	
CCT	2700K, 3000K, 4000K, 2700K - 6500K (Tunable White), RGB	2700K, 3000K, 4000K, 2700K - 6500K (Tunable White), RGB, RGBW	2700K, 3000K, 4000K, 2700K - 6500K (Tunable White), RGB, RGBW	2700K, 3000K, 4000K, 2700K-6500K (Tunable White), RGB, RGBW,	2700K, 3000K, 4000K, 2700K - 6500K (Tunable White), RGB, RGBW	2700K, 3000K, 4000K, 2700K - 6500K (Tunable White), RGB, RGBW	2700K, 3000K, 4000K, 2700K - 6500K (Tunable White), RGB, RGBW	2700K, 3000K, 4000K, 2700K - 6500K (Tunable White), RGB, RGBW	2700K, 3000K, 4000K, 2700K - 6500K (Tunable White), RGB, RGBW	2700K, 3000K, 4000K, 2700K - 6500K (Tunable White), RGB, RGBW	2700K, 3000K, 4000K, 2700K - 6500K (Tunable White), RGB, RGBW	2700K, 3000K, 4000K, 2700K - 6500K (Tunable White), RGB, RGBW	
IP Rating	IP20	IP20	IP20	IP20	IP20	IP20	IP20	IP20	IP20	IP20	IP20	IP20	
Beam	110°	110°	110°	110°	110°	110°	110°	110°	110°	170°	130°	130°	
Maximum Run Length (Single CCT)	50W	100W	100W	100W	100W	100W	100W	100W	100W	100W	100W	100W	
Maximum Run Length (Tunable White, RGB&RGBW)	5m	5m	5m	5m	5m	5m	5m	5m	5m	5m	5m	5m	
Warranty	5 Years	5 Years	5 Years	5 Years	5 Years	5 Years	5 Years	5 Years	5 Years	5 Years	5 Years	5 Years	
Availability	5 business days	5 business days	5 business days	5 business days	5 business days	5 business days	5 business days	5 business days	5 business days	5 business days	5 business days	5 business days	


Luminaire




1

PS10

Accessories



End Caps



Mounting Clips

	LED Power	Lumens	Beam	SDCM	Maximum Single Length Run	Cut Increments
1 Single CCT	10W/m (24V DC)	547lm/m at 3000K	110°	≤1	10m	6.25mm
Tunable White (2700K - 6500K)	10W/m (24V DC)	378lm/m at 2700K	110°	≤2	5m	50mm
RGB	10W/m (24V DC)	241lm/m	110°	N/A	5m	50mm

Key Information		Design		Performance		Driver	
Mounting	Surface, Recessed	Product Family	Inter	Lumen Efficacy	Up to 56lm/W	Non-Dim	Remote
Finish	<div><div>Aluminium</div><div>Textured Black</div></div>	Material	Powdercoated Aluminum, PC Diffuser	CRI (Ra/R9, Single CCT)	95+ (R9: >90)	Phase Cut	Remote
LED CCT	<div><div>2700K</div><div>3000K</div><div>4000K</div><div>2700K-6500K (Tunable White)</div></div>	IP Rating	IP20	Lifetime (Ta 25°C)	>50,000h L90B10	DALI	Remote
	<div><div>RGB</div><div>RGBW</div></div>	Class Rating	Class III	Operating Ambient Temperature	-10°- 35°C	Bluetooth	Remote
		Maximum Supply Length	3 metres				
Diffuser	Opal Diffuser	Strip Compatibility	Inter IN5 Strip Light				
Warranty	5 Years						




- Available Accessories
- PS10 End Cap (Allow 2mm length clearance per end cap)

PS10 Mounting Clip (Allow 2mm width clearance for mounting clips)




Luminaire




1

PS17

Accessories



End Caps



Mounting Clips

	LED Power	Lumens	Beam	SDCM	Maximum Single Length Run	Cut Increments
1 Single CCT	5W/m (24V DC)	327lm/m at 3000K	110°	≤1	20m	6.25mm
	10W/m (24V DC)	654lm/m at 3000K			10m	
	15W/m (24V DC)	981lm/m at 3000K			6.5m	
	20W/m (24V DC)	1307lm/m at 3000K			5m	
Tunable White (2700K - 6500K)	5W/m (24V DC)	301lm/m at 2700K	110°	≤1	5m	11mm
	10W/m (24V DC)	602lm/m at 2700K				
	15W/m (24V DC)	902lm/m at 2700K				
	20W/m (24V DC)	1203lm/m at 2700K				
RGB	10W/m (24V DC)	211lm/m	110°	N/A	5m	50mm
	15W/m (24V DC)	316lm/m				
	20W/m (24V DC)	422lm/m				
RGBW (W at 3000K)	15W/m (24V DC)	427lm/m at 3000K	110°	≤2 (3000K)	5m	50mm
	20W/m (24V DC)	569lm/m at 3000K				

Key Information		Design		Performance		Driver	
Mounting	Surface, Recessed	Product Family	Inter	Lumen Efficacy	Up to 66lm/W	Non-Dim	Remote
Finish	<div><div>Aluminium</div><div>Textured Black</div><div>Textured White</div></div>	Material	Powdercoated Aluminum, PC Diffuser	CRI (Ra/R9, Single CCT)	95+ (R9: >90)	Phase Cut	Remote
LED CCT	<div><div>2700K</div><div>3000K</div><div>4000K</div><div>2700K-6500K (Tunable White)</div></div>	IP Rating	IP20	Lifetime (Ta 25°C)	>50,000h L90B10	DALI	Remote
	<div><div>RGB</div><div>RGBW</div></div>	Class Rating	Class III	Operating Ambient Temperature	-10°- 35°C	Bluetooth	Remote
		Maximum Supply Length	3 metres				
Diffuser	Opal Diffuser	Strip Compatibility	Inter INT0 Strip Light				
Warranty	5 Years						




- Available Accessories
- PS17 End Cap (Allow 2mm length clearance per end cap)


PS17 Mounting Clip (Allow 2mm width clearance for mounting clips)



Luminaire



Accessories



	LED Power	Lumens	Beam	SDCM	Maximum Single Length Run	Cut Increments
1 Single CCT	5W/m (24V DC)	327lm/m at 3000K	110°	≤1	20m	6.25mm
	10W/m (24V DC)	654lm/m at 3000K			10m	
	15W/m (24V DC)	981lm/m at 3000K			6.5m	
	20W/m (24V DC)	1307lm/m at 3000K			5m	
Tunable White (2700K - 6500K)	5W/m (24V DC)	301lm/m at 2700K	110°	≤1	5m	11mm
	10W/m (24V DC)	602lm/m at 2700K				
	15W/m (24V DC)	902lm/m at 2700K				
	20W/m (24V DC)	1203lm/m at 2700K				
RGB	10W/m (24V DC)	211lm/m	110°	N/A	5m	50mm
	15W/m (24V DC)	316lm/m				
	20W/m (24V DC)	422lm/m				
	20W/m (24V DC)	422lm/m				
RGBW(W at 3000K)	15W/m (24V DC)	427lm/m at 3000K	110°	≤2 (3000K)	5m	50mm
	20W/m (24V DC)	569lm/m at 3000K				


Key Information		Design		Performance		Driver	
Mounting	Recessed	Product Family	Inter	Lumen Efficacy	Up to 66lm/W	Non-Dim	Remote
Finish	<div><div>Aluminium</div><div>Textured Black</div><div>Textured White</div></div>	Material	Powdercoated Aluminum, PC Diffuser	CRI (Ra/R9, Single CCT)	95+ (R9: >90)	Phase Cut	Remote
LED CCT	<div><div>2700K</div><div>3000K</div><div>4000K</div><div>2700K-6500K (Tunable White)</div><div>RGB</div><div>RGBW</div></div>	IP Rating	IP20	Lifetime (Ta 25°C)	>50,000h L90B10	DALI	Remote
		Class Rating	Class III	Operating Ambient Temperature	-10°- 35°C	Bluetooth	Remote
		Maximum Supply Length	3 metres				
		Strip Compatibility	Inter IN10 Strip Light				
Diffuser	Opal Diffuser						
Warranty	5 Years						




Available Accessories
PR22 End Cap (Allow 2mm length clearance per end cap)
PR22 Mounting Clip (Allow 2mm width clearance for mounting clips)



Luminaire



Accessories





	LED Power	Lumens	SDCM	Beam	Maximum Single Length Run	Cut Increments
1 2 Single CCT	5W/m (24V DC)	249lm/m at 3000K	≤1	110°	20m	6.25mm
	10W/m (24V DC)	498lm/m at 3000K			10m	
	15W/m (24V DC)	747lm/m at 3000K			6.5m	
	20W/m (24V DC)	995lm/m at 3000K			5m	
	30W/m (24V DC)	1494lm/m at 3000K			6.5m	
1 Tunable White (2700K - 6500K)	5W/m (24V DC)	229lm/m at 2700K	≤1	110°	5m	11mm
	10W/m (24V DC)	458lm/m at 2700K				
	15W/m (24V DC)	687lm/m at 2700K				
	20W/m (24V DC)	916lm/m at 2700K				
	30W/m (24V DC)	1374lm/m at 2700K				
RGB	10W/m (24V DC)	161lm/m	N/A	110°	5m	50mm
	15W/m (24V DC)	241lm/m				
	20W/m (24V DC)	321lm/m				
	30W/m (24V DC)	482lm/m				
RGBW(W at 3000K)	15W/m (24V DC)	325lm/m at 3000K	≤2 (3000K)	110°	5m	50mm
	20W/m (24V DC)	433lm/m at 3000K				
	30W/m (24V DC)	650lm/m at 3000K				

Key Information		Design		Performance		Driver	
Mounting	Surface, Suspended	Product Family	Inter	Lumen Efficacy	Up to 51lm/W	Non-Dim	Remote
Finish	<div><div>Aluminium</div><div>Textured Black</div><div>Textured White</div></div>	Material	Powdercoated Aluminum, PC Diffuser	CRI (Ra/R9, Single CCT)	95+ (R9: >90)	Phase Cut	Remote
LED CCT	<div><div>2700K</div><div>3000K</div><div>4000K</div><div>2700K-6500K (Tunable White)</div><div>RGB</div><div>RGBW</div></div>	IP Rating	IP20	Lifetime (Ta 25°C)	>50,000h L90B10	DALI	Remote
		Class Rating	Class III	Operating Ambient Temperature	-10°- 35°C	Bluetooth	Remote
		Maximum Supply Length	3 metres				
		Strip Compatibility	Inter IN10 Strip Light				
Diffuser	Opal Diffuser						
Warranty	5 Years	Cable Length	3000mm				




Available Accessories
PS35 End Cap (Allow 2mm length clearance per end cap)
PS35 Mounting Clip (Allow 2mm width clearance for mounting clips)
Inter Linear 3000mm Suspension Kit





	LED Power	Lumens	Beam	SDCM	Maximum Single Length Run	Cut Increments
1 Single CCT	5W/m (24V DC)	249lm/m at 3000K	110°	≤1	20m	6.25mm
	10W/m (24V DC)	498lm/m at 3000K			10m	
	15W/m (24V DC)	747lm/m at 3000K			6.5m	
	20W/m (24V DC)	995lm/m at 3000K			5m	
Tunable White (2700K - 6500K)	30W/m (24V DC)	1494lm/m at 3000K			6.5m	
	5W/m (24V DC)	229lm/m at 2700K	110°	≤1	5m	11mm
	10W/m (24V DC)	458lm/m at 2700K				
	15W/m (24V DC)	687lm/m at 2700K				
RGB	20W/m (24V DC)	916lm/m at 2700K				
	30W/m (24V DC)	1374lm/m at 2700K				
	10W/m (24V DC)	161lm/m	110°	N/A	5m	50mm
	15W/m (24V DC)	241lm/m				
RGBW(W at 3000K)	20W/m (24V DC)	321lm/m				
	30W/m (24V DC)	482lm/m				
	15W/m (24V DC)	325lm/m at 3000K	110°	≤2 (3000K)	5m	50mm
	20W/m (24V DC)	433lm/m at 3000K				
	30W/m (24V DC)	650lm/m at 3000K				



Key Information		Design		Performance		Driver	
Mounting	Recessed	Product Family	Inter	Lumen Efficacy	Up to 51lm/W	Non-Dim	Remote
Finish	<div><div>Aluminium</div><div>Textured Black</div><div>Textured White</div></div>	Material	Powdercoated Aluminum, PC Diffuser	CRI (Ra/R9, Single CCT)	95+ (R9: >90)	Phase Cut	Remote
LED CCT	<div><div>2700K</div><div>3000K</div><div>4000K</div><div>2700K-6500K (Tunable White)</div><div>RGB</div><div>RGBW</div></div>	IP Rating	IP20	Lifetime (Ta 25°C)	>50,000h L90B10	DALI	Remote
Diffuser	Opal Diffuser	Class Rating	Class III	Operating Ambient Temperature	-10°- 35°C	Bluetooth	Remote
Warranty	5 Years	Maximum Supply Length	3 metres				
		Strip Compatibility	Inter IN10 Strip Light				



Available Accessories

PR50 End Cap (Allow 2mm length clearance per end cap)

PR50 Mounting Clip (Allow 2mm width clearance for mounting clips)



	LED Power	Lumens (3000K)	Beam	SDCM	Maximum Single Length Run	Cut Increments
1 Single CCT	5W/m (24V DC)	424lm/m at 3000K	110°	≤1	20m	6.25mm
	10W/m (24V DC)	847lm/m at 3000K			10m	
	15W/m (24V DC)	1271lm/m at 3000K			6.5m	
	20W/m (24V DC)	1694lm/m at 3000K			5m	
Tunable White (2700K - 6500K)	5W/m (24V DC)	390lm/m at 2700K	110°	≤1	5m	11mm
	10W/m (24V DC)	780lm/m at 2700K				
	15W/m (24V DC)	1169lm/m at 2700K				
	20W/m (24V DC)	1559lm/m at 2700K				
RGB	10W/m (24V DC)	273lm/m	110°	N/A	5m	50mm
	15W/m (24V DC)	410lm/m				
	20W/m (24V DC)	547lm/m				
	15W/m (24V DC)	553lm/m at 3000K	110°	≤2 (3000K)	5m	50mm
RGBW(W at 3000K)	20W/m (24V DC)	738lm/m at 3000K				

Key Information		Design		Performance		Driver	
Mounting	Recessed	Product Family	Inter	Lumen Efficacy	Up to 86lm/W	Non-Dim	Remote
Finish	<div><div>Aluminium</div></div>	Material	Anodised Aluminum, PC Diffuser	CRI (Ra/R9, Single CCT)	95+ (R9: >90)	Phase Cut	Remote
LED CCT	<div><div>2700K</div><div>3000K</div><div>4000K</div><div>2700K-6500K (Tunable White)</div><div>RGB</div><div>RGBW</div></div>	IP Rating	IP20	Lifetime (Ta 25°C)	>50,000h L90B10	DALI	Remote
Diffuser	Opal Diffuser	Class Rating	Class III	Operating Ambient Temperature	-10°- 35°C	Bluetooth	Remote
Warranty	5 Years	Maximum Supply Length	3 metres				
		Strip Compatibility	Inter IN10 Strip Light				



Available Accessories

FS17 End Cap (Allow 2mm length clearance per end cap)

FS17 Mounting Clip (Allow 2mm width clearance for mounting clips)




Inter Flat


FR25

Linear Light

Luminaire



Accessories



	LED Power	Lumens (3000K)	Beam	SDCM	Maximum Single Length Run	Cut Increments
1 Single CCT	5W/m (24V DC)	424lm/m at 3000K	110°	≤1	20m	6.25mm
	10W/m (24V DC)	847lm/m at 3000K			10m	
	15W/m (24V DC)	1271lm/m at 3000K			6.5m	
	20W/m (24V DC)	1694lm/m at 3000K			5m	
Tunable White (2700K - 6500K)	5W/m (24V DC)	390lm/m at 2700K	110°	≤1	5m	11mm
	10W/m (24V DC)	780lm/m at 2700K				
	15W/m (24V DC)	1169lm/m at 2700K				
	20W/m (24V DC)	1559lm/m at 2700K				
RGB	10W/m (24V DC)	273lm/m	110°	N/A	5m	50mm
	15W/m (24V DC)	410lm/m				
	20W/m (24V DC)	547lm/m				
RGBW(W at 3000K)	15W/m (24V DC)	553lm/m at 3000K	110°	≤2 (3000K)	5m	50mm
	20W/m (24V DC)	738lm/m at 3000K				

Key Information		Design		Performance		Driver	
Mounting	Recessed	Product Family	Inter	Lumen Efficacy	Up to 86lm/W	Non-Dim	Remote
Finish	Aluminium	Material	Anodised Aluminum, PC Diffuser	CRI (Ra/R9, Single CCT)	95+ (R9: >90)	Phase Cut	Remote
LED CCT	2700K	IP Rating	IP20	Lifetime (Ta 25°C)	>50,000h L90B10	DALI	Remote
	3000K			Operating Ambient Temperature	-10°- 35°C	Bluetooth	Remote
	4000K						
	2700K-6500K (Tunable White)						
	RGB	Class Rating	Class III				
Diffuser	Opal Diffuser	Maximum Supply Length	3 metres				
Warranty	5 Years	Strip Compatibility	Inter IN10 Strip Light				



- Available Accessories
- FR25 End Cap (Allow 2mm length clearance per end cap)
- FR25 Mounting Clip (Allow 2mm width clearance for mounting clips)




Inter Angled


AS16

Linear Light

Luminaire



Accessories



	LED Power	Lumens	Beam	SDCM	Maximum Single Length Run	Cut Increments
1 Single CCT	5W/m (24V DC)	446lm/m at 3000K	110°	≤1	20m	6.25mm
	10W/m (24V DC)	892lm/m at 3000K			10m	
	15W/m (24V DC)	1337lm/m at 3000K			6.5m	
	20W/m (24V DC)	1783lm/m at 3000K			5m	
Tunable White (2700K - 6500K)	5W/m (24V DC)	410lm/m at 2700K	110°	≤1	5m	11mm
	10W/m (24V DC)	820lm/m at 2700K				
	15W/m (24V DC)	1231lm/m at 2700K				
	20W/m (24V DC)	1641lm/m at 2700K				
RGB	10W/m (24V DC)	288lm/m	110°	N/A	5m	50mm
	15W/m (24V DC)	432lm/m				
	20W/m (24V DC)	575lm/m				
RGBW(W at 3000K)	15W/m (24V DC)	582lm/m at 3000K	110°	≤2 (3000K)	5m	50mm
	20W/m (24V DC)	776lm/m at 3000K				


Key Information		Design		Performance		Driver	
Mounting	Recessed	Product Family	Inter	Lumen Efficacy	Up to 91lm/W	Non-Dim	Remote
Finish	Aluminium Textured Black	Material	Powdercoated Aluminum, PC Diffuser	CRI (Ra/R9, Single CCT)	95+ (R9: >90)	Phase Cut	Remote
LED CCT	2700K	IP Rating	IP20	Lifetime (Ta 25°C)	>50,000h L90B10	DALI	Remote
	3000K			Operating Ambient Temperature	-10°- 35°C	Bluetooth	Remote
	4000K						
	2700K-6500K (Tunable White)						
	RGB	Class Rating	Class III				
Diffuser	Opal Diffuser	Maximum Supply Length	3 metres				
Warranty	5 Years	Strip Compatibility	Inter IN10 Strip Light				




- Available Accessories
- AS16 End Cap (Allow 2mm length clearance per end cap)
- AS16 Mounting Clip (Allow 2mm width clearance for mounting clips)



Luminaire




Accessories



	LED Power	Lumens	Beam	SDCM	Maximum Single Length Run	Cut Increments
1 Single CCT	5W/m (24V DC)	127lm/m at 3000K	110°	≤1	20m	6.25mm
	10W/m (24V DC)	254lm/m at 3000K			10m	
	15W/m (24V DC)	380lm/m at 3000K			6.5m	
	20W/m (24V DC)	507lm/m at 3000K			5m	
Tunable White (2700K - 6500K)	5W/m (24V DC)	117lm/m at 2700K	110°	≤1	5m	11mm
	10W/m (24V DC)	233lm/m at 2700K				
	15W/m (24V DC)	350lm/m at 2700K				
	20W/m (24V DC)	467lm/m at 2700K				
RGB	10W/m (24V DC)	82lm/m	110°	N/A	5m	50mm
	15W/m (24V DC)	123lm/m				
	20W/m (24V DC)	164lm/m				
	20W/m (24V DC)	166lm/m at 3000K				
RGBW(W at 3000K)	15W/m (24V DC)	166lm/m at 3000K	110°	≤2 (3000K)	5m	50mm
	20W/m (24V DC)	221lm/m at 3000K				


Key Information		Design		Performance		Driver	
Mounting	Recessed	Product Family	Inter	Lumen Efficacy	Up to 26lm/W	Non-Dim	Remote
Finish	<input type="checkbox"/> Textured White	Material	Powdercoated Aluminum, PC Diffuser	CRI (Ra/R9, Single CCT)	95+ (R9: >90)	Phase Cut	Remote
LED CCT	<input type="checkbox"/> 2700K	IP Rating	IP20	Lifetime (Ta 25°C)	>50,000h L90B10	DALI	Remote
	<input type="checkbox"/> 3000K	Class Rating	Class III	Operating Ambient Temperature	-10°- 35°C	Bluetooth	Remote
	<input type="checkbox"/> 4000K	Maximum Supply Length	3 metres				
	<input type="checkbox"/> 2700K-6500K (Tunable White)	Strip Compatibility	Inter IN10 Strip Light				
	<input type="checkbox"/> RGB						
	<input type="checkbox"/> RGBW						
Diffuser	Opal Diffuser						
Warranty	5 Years						




Available Accessories
CR100 End Cap (Allow 2mm length clearance per end cap)
CR100 Mounting Kit



Luminaire



Accessories



	LED Power	Lumens (3000K)	Beam	SDCM	Maximum Single Length Run	Cut Increments
1 2 Single CCT	5W/m (24V DC)	520lm/m at 3000K	170°	≤1	20m	6.25mm
	10W/m (24V DC)	1039lm/m at 3000K			10m	
	15W/m (24V DC)	1559lm/m at 3000K			6.5m	
	20W/m (24V DC)	2078lm/m at 3000K			5m	
1 Tunable White (2700K - 6500K)	5W/m (24V DC)	478lm/m at 2700K	170°	≤1	5m	11mm
	10W/m (24V DC)	956lm/m at 2700K				
	15W/m (24V DC)	1434lm/m at 2700K				
	20W/m (24V DC)	1912lm/m at 2700K				
RGB	10W/m (24V DC)	335lm/m	170°	N/A	5m	50mm
	15W/m (24V DC)	503lm/m				
	20W/m (24V DC)	671lm/m				
RGBW(W at 3000K)	15W/m (24V DC)	678lm/m at 3000K	170°	≤2 (3000K)	5m	50mm
	20W/m (24V DC)	905lm/m at 3000K				



Key Information		Design		Performance		Driver	
Mounting	Surface, Suspended	Product Family	Inter	Lumen Efficacy	Up to 106lm/W	Non-Dim	Remote
Finish	<input checked="" type="checkbox"/> Textured Black	Material	Anodised Aluminum, PC Diffuser	CRI (Ra/R9, Single CCT)	95+ (R9: >90)	Phase Cut	Remote
LED CCT	<input type="checkbox"/> 2700K	IP Rating	IP20	Lifetime (Ta 25°C)	>50,000h L90B10	DALI	Remote
	<input type="checkbox"/> 3000K	Class Rating	Class III	Operating Ambient Temperature	-10°- 35°C	Bluetooth	Remote
	<input type="checkbox"/> 4000K	Maximum Supply Length	3 metres				
	<input type="checkbox"/> 2700K-6500K (Tunable White)	Strip Compatibility	Inter IN10 Strip Light				
	<input type="checkbox"/> RGB	Cable Length	3000mm				
	<input type="checkbox"/> RGBW						
Diffuser	Opal Diffuser						
Warranty	5 Years						





Available Accessories
RP30 End Cap
RP30 Mounting Clip
Inter Linear 3000mm Suspension Kit



Luminaire



Accessories



End Caps

Mounting Clips

	LED Power	Lumens (3000K)	Beam	SDCM	Maximum Single Length Run	Cut Increments
1 Single CCT	5W/m (24V DC)	493lm/m at 3000K	130°	≤1	20m	6.25mm
	10W/m (24V DC)	987lm/m at 3000K			10m	
	15W/m (24V DC)	1480lm/m at 3000K			6.5m	
	20W/m (24V DC)	1973lm/m at 3000K			5m	
Tunable White (2700K - 6500K)	5W/m (24V DC)	454lm/m at 2700K	130°	≤1	5m	11mm
	10W/m (24V DC)	908lm/m at 2700K				
	15W/m (24V DC)	1362lm/m at 2700K				
	20W/m (24V DC)	1816lm/m at 2700K				
RGB	10W/m (24V DC)	318lm/m	130°	N/A	5m	50mm
	15W/m (24V DC)	478lm/m				
	20W/m (24V DC)	637lm/m				
RGBW(W at 3000K)	15W/m (24V DC)	644lm/m at 3000K	130°	≤2 (3000K)	5m	50mm
	20W/m (24V DC)	859lm/m at 3000K				



Key Information		Design		Performance		Driver	
Mounting	Surface	Product Family	Inter	Lumen Efficacy	Up to 100lm/W	Non-Dim	Remote
Finish	Aluminium	Material	Anodised Aluminum, PC Diffuser	CRI (Ra/R9, Single CCT)	95+ (R9: >90)	Phase Cut	Remote
LED CCT	2700K	IP Rating	IP20	Lifetime (Ta 25°C)	>50,000h L90B10	DALI	Remote
	3000K	Class Rating	Class III	Operating Ambient Temperature	-10°- 35°C	Bluetooth	Remote
	4000K	Maximum Supply Length	3 metres				
	2700K-6500K (Tunable White)	Strip Compatibility	Inter INT0 Strip Light				
Diffuser	Opal Diffuser						
Warranty	5 Years						





- Available Accessories
- DRS20 End Cap (Allow 2mm length clearance per end cap)
- DRS20 Mounting Clip (Allow 2mm width clearance for mounting clips)



Luminaire



Accessories



End Caps

Mounting Clips

	LED Power	Lumens (3000K)	Beam	SDCM	Maximum Single Length Run	Cut Increments
1 Single CCT	5W/m (24V DC)	493lm/m at 3000K	130°	≤1	20m	6.25mm
	10W/m (24V DC)	987lm/m at 3000K			10m	
	15W/m (24V DC)	1480lm/m at 3000K			6.5m	
	20W/m (24V DC)	1973lm/m at 3000K			5m	
Tunable White (2700K - 6500K)	5W/m (24V DC)	454lm/m at 2700K	130°	≤1	5m	11mm
	10W/m (24V DC)	908lm/m at 2700K				
	15W/m (24V DC)	1362lm/m at 2700K				
	20W/m (24V DC)	1816lm/m at 2700K				
RGB	10W/m (24V DC)	318lm/m	130°	N/A	5m	50mm
	15W/m (24V DC)	478lm/m				
	20W/m (24V DC)	637lm/m				
RGBW(W at 3000K)	15W/m (24V DC)	644lm/m at 3000K	130°	≤2 (3000K)	5m	50mm
	20W/m (24V DC)	859lm/m at 3000K				

Key Information		Design		Performance		Driver	
Mounting	Surface	Product Family	Inter	Lumen Efficacy	Up to 100lm/W	Non-Dim	Remote
Finish	Aluminium	Material	Anodised Aluminum, PC Diffuser	CRI (Ra/R9, Single CCT)	95+ (R9: >90)	Phase Cut	Remote
LED CCT	2700K	IP Rating	IP20	Lifetime (Ta 25°C)	>50,000h L90B10	DALI	Remote
	3000K	Class Rating	Class III	Operating Ambient Temperature	-10°- 35°C	Bluetooth	Remote
	4000K	Maximum Supply Length	3 metres				
	2700K-6500K (Tunable White)	Strip Compatibility	Inter INT0 Strip Light				
Diffuser	Opal Diffuser						
Warranty	5 Years						




- Available Accessories
- DSS20 End Cap (Allow 2mm length clearance per end cap)
- DSS20 Mounting Clip (Allow 2mm width clearance for mounting clips)




Inter Single CCT

Strip Light


Luminaire




1



IN10 (10mm)



2



INS (5mm)

	LED Power	Lumens (at 3000K)	Beam	No. of LED's	LED Pitch	Maximum Single Length Run	Cut Increments
1 Inter IN10 Strip Light	5W/m (24V DC)	615lm/m	120°	160LEDs/m	6.25mm	20m	6.25mm
	10W/m (24V DC)	1233lm/m				10m	
	15W/m (24V DC)	1850lm/m				6.5m	
	20W/m (24V DC)	2467lm/m				5m	
2 Inter INS Strip Light	10W/m (24V DC)	1233lm/m	120°	160LEDs/m	6.25mm	5m	6.25mm

Key Information

Mounting

3M Adhesive tape

LED CCT

2700K

3000K

4000K

Warranty

5 Years

Maximum Supply Length

20 metres

Maximum Run Power

100W

Design

Product Family

Inter

Material

3oz Flexible copper-clad PCB

IP Rating

IP20

Class Rating

Class III

Performance

Lumen Efficacy

Up to 125lm/W

CRI (Ra/R9)

95+ (R9: >90)

Rf (TM-30)

94

Rg (TM-30)

101

Lifetime (Ta 25°C)

>50,000h L90B10

Operating Ambient Temperature

-10°- 35°C

SDCM

≤1

Driver

Non-Dim

Remote

Phase Cut

Remote

DALI

Remote

Bluetooth

Remote

Available Accessories

LED Strip Roller (for profile installation)


Edition 20.2.24 | Product design and technical data may be subject to change

Linear | Configure online at unios.com/interstrip


Inter Tunable White

Strip Light


Luminaire




1



IN10 (10mm)



2



INS (5mm)

	LED Power	Lumens (at 2700K)	Beam	SDCM	No. of LED's	LED Pitch	Maximum Single Length Run	Cut Increments
1 Inter IN10 Tunable White Strip Light	5W/m (24V DC)	568lm/m	120°	≤1	180LEDs/m	11mm	5m	50mm
	10W/m (24V DC)	1135m/m						
	15W/m (24V DC)	1703lm/m						
	20W/m (24V DC)	2270lm/m						
2 Inter INS Tunable White Strip Light	10W/m (24V DC)	852lm/m	120°	≤2	240LEDs/m	8.3mm	5m	11mm

Key Information

Mounting

3M Adhesive tape

LED CCT

2700K-6500K (Tunable White)

Warranty

5 Years

Maximum Supply Length

20 metres

Maximum Run Power

100W

Design

Product Family

Inter

Material

3oz Flexible copper-clad PCB

IP Rating

IP20

Class Rating

Class III

Performance

Lumen Efficacy

Up to 125lm/W

CRI (Ra/R9)

95+ (R9: >90)

Rf (TM-30)

94

Rg (TM-30)

101

Lifetime (Ta 25°C)

>50,000h L90B10

Operating Ambient Temperature

-10°- 35°C

Driver

DALI

Remote

Bluetooth

Remote

Available Accessories

LED Strip Roller (for profile installation)

Edition 20.2.24 | Product design and technical data may be subject to change


Linear | Configure online at unios.com/interstrip

55


Inter RGB

Strip Light


Luminaire




1



IN10 (10mm)



2



IN5 (6mm)

	LED Power	Lumens (RGB)	Beam	Maximum Single Length Run
1 Inter IN10 RGB Strip Light	10W/m (24V DC)	398lm/m	120°	5m
	15W/m (24V DC)	597lm/m		
	20W/m (24V DC)	796lm/m		
2 Inter IN5 RGB Strip Light	10W/m (24V DC)	543lm/m	120°	5m

Key Information

Mounting

3M Adhesive tape

LED Colour

RGB

Warranty

5 Years

Maximum Supply Length

20 metres

Maximum Run Power

100W

Design

Product Family

Inter

Material

3oz Flexible copper-clad PCB

IP Rating

IP20

Class Rating

Class III

Cut Lengths

50mm

LED Pitch

8.3mm

No. of LED's

120LEDs/m

Performance

Lumen Efficacy

Up to 54lm/W

CRI (Ra/R9)

N/A

Rf (TM-30)

N/A

Rg (TM-30)

N/A

Lifetime (Ta 25°C)

>50,000h L90B10

Operating Ambient Temperature

-10°- 35°C

SDCM

N/A


Driver

DALI

Remote

Bluetooth

Remote




Available Accessories
LED Strip Roller (for profile installation)




Inter RGBW

Strip Light

Luminaire



1



IN10 (10mm)

	LED Power	Lumens (3000K)	Lumens (RGB)	Beam	Maximum Single Length Run
1 Inter IN10 RGBW Strip Light	15W/m (24V DC)	805lm/m	359lm/m	120°	5m
	20W/m (24V DC)	1074lm/m	479lm/m		

Key Information

Mounting

3M Adhesive tape

LED CCT

RGBW (3000K)

Warranty

5 Years

Maximum Supply Length

20 metres

Maximum Run Power

100W

Design

Product Family

Inter

Material

3oz Flexible copper-clad PCB

IP Rating

IP20

Class Rating

Class III

Cut Lengths

50mm

LED Pitch

8.3mm

No. of LED's

240LEDs/m

Performance

Lumen Efficacy

Up to 107lm/W

CRI (Ra/R9)

95+ (R9: >90)

Rf (TM-30)

91

Rg (TM-30)

98

Lifetime (Ta 25°C)

>50,000h L90B10

Operating Ambient Temperature

-10°- 35°C

SDCM

≤2 (3000K)


Driver

DALI

Remote

Bluetooth

Remote



Available Accessories
LED Strip Roller (for profile installation)




About Us



Three-time Good Design Award winner, including a Gold Award.



Unios Toolbox – a platform built for clarity, supporting your workflow anytime, anywhere.



3K+ users

With experience centres in Australia and Vietnam, and offices in Korea and Singapore, we're here to support your region end-to-end.

APAC Lighting Partner

Winner of the Red Dot Award with the Pandia Glass Series.



reddot winner 2025 lighting design

Special Thanks

This publication wouldn't be possible without the ongoing support of our project partners, distributors and photographers who have assisted in providing content.

More Information

For additional technical information and to access our full library, visit unios.com. Our library contains a comprehensive database of BIM objects, IES files and product imagery.

Instagram: [instagram.com/unioslight](https://www.instagram.com/unioslight)
Facebook: [facebook.com/unioslight](https://www.facebook.com/unioslight)
LinkedIn: [linkedin.com/company/unios](https://www.linkedin.com/company/unios)
Youtube: [unios.com/youtube](https://www.youtube.com/unios)
Pinterest: [pinterest.com/unioslight](https://www.pinterest.com/unioslight)
Twitter: twitter.com/unioslight



Locate your nearest
Unios distributor or office

unios.com/find-us