
Tetra

Panel Light

T-Bar



Plaster




Surface Mounted




Suspended




Sizes




1 300x600 T-Bar




2 600x600 T-Bar




3 300x1200 T-Bar




4 600x1200 T-Bar




1 300x600 Plaster




2 600x600 Plaster




3 300x1200 Plaster




1 300x600 Surface Mounted




2 600x600 Surface Mounted




3 300x1200 Surface Mounted



1 300x600 Suspended



2 600x600 Suspended



3 300x1200 Suspended

		LED Power	Lumens (at 4000K)	Beam	Weight (T-Bar)
1	**300 x 600**	13W (350mA)	1727lm	90°	0.7KG
		18W (500mA)	2467lm		
2	**600 x 600**	18W (500mA)	2467lm	90°	1.3KG
		27W (750mA)	3700lm		
3	**300 x 1200**	18W (500mA)	2444lm	90°	1.7KG
		27W (750mA)	3666lm		
4	**600 x 1200**	36W (1000mA)	4934lm	90°	3.0KG

Key Information	
Mounting	Ceiling Recessed, Ceiling Surface, Ceiling Suspended
Finish	Matt White
LED CCT	3000K 4000K 2700K-6500K (Tunable White)
Warranty	5 Years

Design	
Material	Aluminium Frame, PS Diffuser
IP Rating	IP40 (Room Side)
Class Rating	Class II
Insulation Rating	IC-4

Performance	
Lumen Efficacy	Up to 134lm/W
CRI (Ra/R9)	90+ (R9: >50)
UGR (70/50/20)	<19
Lifetime (Ta 25°C)	>70,000h L90B10
Operating Ambient Temperature	-10°- 35°C
SDCM	≤3
COI Compliance Model Requirements	4000K

Driver	
Non-Dim	Remote
Phase Cut	Remote
DALI	Remote
Bluetooth	Remote

